

**60 CELL MODEL**

ELECTRICAL CHARACTERISTICS			
RATED POWER (Wp)	<b>250</b>	<b>255</b>	<b>260</b>
OPEN CIRCUIT VOLTAGE (Voc)	37.80 V	37.90 V	38.00 V
MAXIMUM POWER VOLTAGE (Vmp)	31.00 V	31.20 V	31.40 V
SHORT CIRCUIT CURRENT (Isc)	8.62 A	8.64 A	8.77 A
MAXIMUM POWER CURRENT (Imp)	8.10 A	8.20 A	8.30 A
MODULE EFFICIENCY (%)	15.0	15.3	15.6
OUTPUT TOLERANCE (%)		±3	
CELLS PER MODULE		60	
CELL LAYOUT		10x6	
MAXIMUM SYSTEM VOLTAGE		1000 VDC	

ELECTRICAL CONNECTION	
JUNCTION BOX	IP 65
OUTPUT TERMINAL	MC 4 TYPE / COMPATIBLE
PROTECTION	SCHOTTKY BY – PASS DIODES

MECHANICAL CHARACTERISTICS	
MODULE DIMENSIONS (mm)	1668 x 997 x 46
WEIGHT (KG.APPROX)	24

ABSOLUTE MAXIMUM RATINGS	
OPERATING TEMPERATURE	-40° C to + 85° C

GENERAL	
FRAME	ANODIZED ALUMINUM
FRAME COLOUR	NATURAL MATT / GLOSSY STEEL FINISH (OPTIONAL)

TEMPERATURE CO-EFFICIENT		
$\alpha_{Isc}$	$\beta_{Voc}$	$\gamma_{Pmp}$
%/°C	%/°C	%/°C
+0.1	-0.36	-0.5
<b>NOCT</b>	47±2°C	

WARRANTY	
5 YEARS PRODUCT WARRANTY	
0 - 10 YEARS FOR 90% OF RATED POWER	
10 - 25 YEARS FOR 80% OF RATED POWER	

**INDIA**  
 HHV SOLAR TECHNOLOGIES PVT. LTD  
 No. 31,32,33,34 & 37, KIADB Industrial Area  
 Dabaspet, Nelamangala Taluk  
 Bangalore Rural 562 111, Karnataka, INDIA  
 Ph: + 91 80 2263 3700 Fax: +91 80 2263 3811  
 E-mail: [info@hvsolar.com](mailto:info@hvsolar.com) ; [www.hvsolar.com](http://www.hvsolar.com)

**INTERNATIONAL OFFICES**

<b>NORTH AMERICA</b> HHV SOLAR INC. 1914, Tynemoore court Smyrna, Georgia 30080, USA	<b>AUSTRALIA</b> HHV SOLAR PTY. LTD 38, Concord Terrace Atwell, WA 6164, AUSTRALIA
---	---

